



# Product information

## SPECIFICATION FOR THE SELF-ADHESIVE BACKING USED ON SILICONE SHEETS AND STRIPS

**PRODUCT DESCRIPTION** - a permanent tape with tissue carrier, the adhesive is a modified acrylic, offering good UV light and chemical resistance together with very high performance over a wide temperature range. The liner is a two sided release system.

CONSTRUCTION	SUBSTANCE	THICKNESS
Adhesive	50gsm	
Tissue	12gsm Adhesive & Carrier	115 micron
Adhesive	55gsm	
Liner	90gsm Liner	75 micron

**APPLICATIONS** - a high performance, high temperature resistant modified acrylic adhesive at high coatweight makes 2881 especially suitable for splicing applications especially where high temperatures are involved. The product is also suitable for name plate and foam laminating applications.

ADHESIVE PROPERTIES		20 mins	24 hours	Test Method
Adhesion to steel	open side	700 N/M	1000 N/M	PSMA DST 1
	closed side	700 N/M	1000 N/M	PSMA DST 1
Shear adhesion	open side	40 hours		PSMA DST 2
	closed side	40 hours		PSMA DST 2
Loop tack	open side	450 N/M		PSMA DST 4
	closed side	450 N/M		PSMA DST 4

THERMAL PROPERTIES	
Recommended service temperature range	-10°C to 180°C
Application temperature range	5°C to 60°C

**Minimum shelf life when stored in closed box away from direct heat sources and light - 2 YEARS**

Issue 2 February 1998

Check out the download area of our website  
[www.j-flex.co.uk](http://www.j-flex.co.uk) for other product information



Clockpress Limited  
 Registered in England.  
 Registration No. 2448048  
 Registered Office:  
 St Hugh's, 23 Newport,  
 Lincoln LN1 3DN

### J-FLEX RUBBER PRODUCTS

*Engineering Rubber Components & Specialised Sheeting Products*

Unit 1, London Road Business Park, Retford,  
 Nottinghamshire, England DN22 6HG

tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409  
[www.j-flex.co.uk](http://www.j-flex.co.uk)

