



Product information

“COMMERCIAL SILICONE SPONGE” (SHEETING & EXTRUSION GRADE)

TECHNICAL DATA		
PROPERTY	NORM	TYPICAL VALUE
Temperature Resistance (°C)	-60°C / +200°C Continuous	
Compression Set(%) 22hrs @ 70°C	BS EN ISO 1856 'A'	10%
Compression Stress @ 40% strain (KPa)	BS EN ISO 3386 Part 1,2	90 (+/-40)
Tensile Strength (N.mm ²)	BS EN ISO 1798	1.2
Elongation @ Break (%)	BS EN ISO 1798	200%
PHYSICAL DATA		
Density (Kg/m ³)	BS EN ISO 845	Nominal 250 (+/-40) dependent upon exact thickness
Standard Colour	Off White – other colours possible upon request	
Available in Rolls: 1000mm wide x 10m long	Thicknesses: 1.5, 2.0, 3.0, 4.0, 5.0, 6.0, 8.0, 10.0 & 12.0mm	
Available in Sheets: 1000mm x 600mm	Thicknesses: 16.0, 20.0 & 25.4mm	



ISSUE 3

October 2002

Check out the download area of our website
www.j-flex.co.uk for other product information



Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS

Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG
tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

