



Product information

DARK GREY (RAL 7024) FLAME RETARDANT LOW SMOKE / LOW TOXIC SILICONE RUBBER SHEETING - QUALITY : 72 LCH1



PROPERTY	TEST METHOD	UNIT OF MEASUREMENT	VALUE
HARDNESS	ASTM D2240	° SHORE A	70° (+/-5°)
TENSILE STRENGTH	DIN 53504 Die S1	MPa	5.5 mln
ELONGATION @ BREAK	DIN 53504 Die S1	%	130Min
TEMPERATURE RANGE	-60°C to +230°C Continuous		

SPECIFICATIONS

This low combustion Silicone Rubber meets the requirements of BS 6853 Cat 1 and LUL Code of Practice for Fire Safety. (Materials used in the Underground; August 1990).

It also meets the requirements of NFF 16-101 Grid 5,6,7,8,9,10,11,12,13 & 15.

Full Flammability Characteristics of material can be supplied upon request.

Issue 2

February 2005

Check out the download area of our website www.j-flex.co.uk for other product information



Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS *Engineering Rubber Components & Specialised Sheeting Products*

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG
tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

