



Product information

TECHNICAL DATA SHEET

“Specification Neoprene Sheet”

Manufactured and released to BS2752: C40: 1990

Quality No.	:	3250 - 05
Polymer	:	Chloroprene
Colour	:	Black
Durometer	:	40° (+5 / -4)
Tensile Strength	:	13 MPa minimum per BS 903: Part A2
Elongation	:	250% minimum per BS 903: Part A2
Surface	:	Smooth or Liner impressed, clean or dusted
Roll Width	:	1200mm
Roll Length	:	Up to 50 metres
Stock Thicknesses:	:	0.5mm(+/-0.075) & 0.8mm(+/-0.075) (Smooth Surface Finish Only)

Applications and Attributes

3250 - 05 is a specification grade of chloroprene rubber sheet that exhibits excellent abrasion resistance and very good flame and fuel resistance. 3250 - 05 can be used in gasket or diaphragm applications that are exposed to fuel or harsh weather conditions.

February 2003

Check out the download area of our website
www.j-flex.co.uk for other product information



A member of the
Gasket Cutters
Association



Certificate No. RS 27920
Approved to
BS EN ISO 9001:2000

Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS

Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG

tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

