

DATE: 1/1/03

NEOPRENE / NYLON DIAPHRAGM SHEET J-FLEX QUALITY NO: HN45 – 2.00MM THICK

MATERIAL SPECIFICATION:

2.00mm Thick Neoprene /Nylon Diaphragm Sheet - Smooth Finish Suitable for many applications including compressed air, water, oxygen and ozone.

SPECIFICATION DETAILS

◆ POLYMER TYPE	:	POLYCHLOROPRENE (NEOPRENE)
◆ COLOUR	:	BLACK
◆ TEXTILE TYPE	:	100 % NYLON
◆ NO. OF PLYS	:	2
◆ FINISHED THICKNESS	:	2.00mm (+/-0.20)
◆ TENSILE BREAKING STRENGTH	:	400Kg / 50mm Warp
◆ TENSILE BREAKING STRENGTH	:	350Kg / 50mm Weft
◆ APPROX. BURST STRENGTH	:	>700 p.s.i. (Tested to BS EN 12332-2:2002)

OPERATING TEMPERATURE : -30° to + 100°C

Notes: Good resistance to atmospheric ageing, alcohols, dilute acids and bases, salt solutions, light motor oils, flex cracking.

Typical uses are thin gauge diaphragms, gaskets and fabrication requiring burst strength and good flexibility.

Check out the download area of our website
www.j-flex.co.uk for other product information



Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS

Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG

tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

