



Product information

PEROXIDE FREE – PLATINUM CURED TRANSLUCENT SILICONE SHEETING 60° SHORE'A' QUALITY: PLAT60



DESCRIPTION:

“Premium Grade Peroxide Free” silicone sheeting is designed to be used where higher physical properties are required and in applications that require a low volatile and low outgassing material. Most volatiles and outgassing occur in rubber from the peroxide catalysts that are used to cure the material. This material used a very clean, high end platinum cure system that is peroxide free. This type of cure system is most common among medical grade materials. We have tailored it to fit in many industrial applications where peroxide can cause problems to the end user. The material is available in continuous rolls or sheets. It is resistant to extreme high and low temperatures, and is proven to be an excellent gasketing material.

FEATURES:

- Extremely Low Volatile / Low Outgassing
- Extreme High & Low Temperature Resistance
- UV / Ozone Resistant
- All FDA approved ingredients
- Low Compression Set

SPECIFICATIONS:

- ZZR-765F
- FDA / USD
- ASTM D2000

PHYSICAL PROPERTIES	Typical Values	Test Method
Specific Gravity	1.18 G/CC	ASTM D297
Durometer	60° (+/-5)	ASTM D2240
Tensile Strength	1000	ASTM D412
Elongation	600%	ASTM D 412
Tear	135 ppi Die “B”	ASTM D624
Temperature Range	Up to 230°C	

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.

Issue 4

February 2011

Check out the download area of our website www.j-flex.co.uk for other product information



Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS

Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG
tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

