



Product information

SILICONE RUBBER COATED FIBREGLASS ALPHA MARITEX STYLE 3101-1-SS

BASE FABRIC:	VALUES	METHODS
WEIGHT:	430 g/m ² (+/- 5%)	DIN EN 12127
WEAVE:	Cross Twill	DIN ISO 9354
YARN CONSTRUCTION:		DIN EN 12654
Warp - Weft -	EC9 68x2 (+/- 5%) EC9 68x2 (+/- 5%)	
THREAD COUNT:		DIN EN 1049
Warp ends - Weft ends -	20,0 1/cm (+/- 5%) 10,0 1/cm (+/- 5%)	
FINISHED PRODUCT	VALUES	METHODS
COATING:	Coated with high temperature flame retardant silver grey silicone rubber on one side, continuous temperature resistance 250°C	
WEIGHT:	480 g/m ² (+/- 10%)	DIN EN 12127
THICKNESS:	0,45mm (+/- 10%)	DIN EN ISO 4603/E
TENSILE STRENGTH:		DIN ISO 4606
Warp - Weft -	>4.000 N/ 5 cm >3.000 N/ 5 cm	
TEMPERATURE RESISTANCE:	550°C continuous	
COLOUR / COATING:	Silver/Grey Silicone Rubber on one side	
APPROVALS:	DIN 4102 A2	

Issue 1

April 2008

Check out the download area of our website
www.j-flex.co.uk for other product information



Clockpress Limited
Registered in England.
Registration No. 2448048
Registered Office:
St Hugh's, 23 Newport,
Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS
Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
Nottinghamshire, England DN22 6HG
tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

