



Product information

J-FLEX VITON® SPONGE



J-Flex Viton Sponge is a closed cell formulation that is manufactured with a continuous skin on both sides. The skin makes the sheet stronger and more tear resistant and even when the surface skin is punctured or cut, the sheets will not allow the passage of air or fluid between cells. The non-absorbent sheets are highly compressible, resilient, lightweight and provide good thermal insulation.

Like dense Viton, J-Flex Viton Sponge is generally resistant to aliphatic and aromatic hydrocarbons, oil, fuels, ozone and weather, lubricants, and animal or vegetable oils. It is also resistant to acids and hot water.

J-Flex Viton Sponge sheets have a service temperature of -25°C to 204°C, however, elevated temperatures while under compression will have an adverse effect on the resilience of this material.

TYPICAL PHYSICAL PROPERTIES					
Thickness	1/8" (3.18mm)	1/4" (6.35mm)	3/8" (9.53mm)	1/2" (12.7mm)	3/4" (19.05mm)
Water Pick-Up (% Weight Increase)	0.00%	0.02%	0.06%	0.01%	0/01%
Compression Set					
(22 hours at 24°C)	27%	13%	14%	17%	17%
(22 hours at 70°C)	100%	100%	100%	100%	100%
Low Temperature Brittleness (°C)	-25°C	-25°C	-25°C	-25°C	-25°C
Compression Deflection (psi)					
(25% Deflection - original)	6.5	5.5	4.0	3.5	3.5
(25% Deflection - 7 days @ 204°C)	9.0	7.5	6.0	5.0	5.0
Density - lbs per cubic foot	19	17	15	10	10
Thickness Tolerance (inches)	+0.050/-0.030	+0.060/-0.060	+0.080/-0.080	+0.125/-0.125	+0.125/-0.125

Viton® is the registered trademark of DuPont Performance Elastomers.

J-Flex are approved DuPont Viton® licensees - duly authorised to market and distribute 100% Genuine Viton® Sheeting Products.

Issue 1

December 2007

Check out the download area of our website www.j-flex.co.uk for other product information



Clockpress Limited
 Registered in England.
 Registration No. 2448048
 Registered Office:
 St Hugh's, 23 Newport,
 Lincoln LN1 3DN

J-FLEX RUBBER PRODUCTS

Engineering Rubber Components & Specialised Sheeting Products

Unit 1, London Road Business Park, Retford,
 Nottinghamshire, England DN22 6HG
 tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409
www.j-flex.co.uk

